

**HYDRAULIC**

**711**



711 hose is a medium-pressure, 4-wire spiral constructed hose offered in two large I.D. sizes. Designed for high-impulse, long-life applications like injection molding.

- 3000 psi constant working pressure

**Application:** Petroleum base hydraulic fluids and lubricating oils.

**Inner Tube:** Synthetic rubber.

**Reinforcement:** Four spiral steel wire.

**Cover:** Synthetic rubber, MSHA accepted.

**Temperature Range:** -40°F to +212°F (-40°C to +100°C).

**Fittings:** 71 Series - pg. B-71.

**711**

**Hydraulic**

J1942 / USCG HF / DNV / ABS



# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Parkrimp 71 Series
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m	
711-24	1-1/2	38,0	2.07	53	3000	21,0	22	560	2.01	2,99	●
711-32	2	51,0	2.59	66	3000	21,0	28	710	2.75	4,09	●



**威士乐北京分部**

北京经济技术开发区国际企业大道67号

电话：010 5719 3966

传真：010 5945 8268

邮件：parkerhose@163.com

网站：[www.vexroth.com](http://www.vexroth.com)

**威士乐上海分部**

上海金山区联东U谷丙16号

电话：021 2304 6578

传真：021 3965 1541

邮件：parkerhose@126.com

网站：[www.vexroth.com](http://www.vexroth.com)

- See Section C for Parkrimp Assembly Instructions.
- Temperature Range of other media listed in Section E.